
## **Acoustic Panel**

Housing:


Aluminium frame with acoustic membrane (without illumination)

Design: SATTLER









fabric characteristics o sound absorption coefficient  $\alpha_s = 0,55$ 

In the range of 500 - 2,000 Hz relevant for human speech, an absorption maximum of up to 0.82 is reached.

o fire protection class B1 o fabric colour white

	Size: Ø mm	Inches	LED Watt	Lumen 1)	Weight 2) kg/lbs	Item No.	LED	Dimmin	ng	Finishes	Power supply cable	Mounting version
Sizes											oub.o	
	Ø 1272 mm Ø 1582 mm	50.1" 62.3"			3.5 / 7.7 4.2 / 9.2	1042. 1043.	x x. x x.	x x. x x.	x x. x x.	x x. x x.	x x x. x x x.	x x
	1260 x 1260 mm 1560 x 1560 mm	49.6 x 49.6" 61.4 x 61.4"			6.5 / 14.3 8.2 / 18.0	1062. 1063.	x x. x x.		x x. x x.	x x. x x.	xxx. xxx.	x x
Finishes (Standard)		acoustic fabric w	/hite			xxx.	x x.	x x.	x x.	x x.	xxx.	х
		4 point suspension	on		Standard	xxx.	x x.	x x.	x x.	x x.	x x x.	В.
		Direct ceiling mo	ounting		Optional	x x x.	х х.	x x.	x x.	x x.	x x x.	Н.
Mounting version with steel cable length 5000 mm												
						XXX.	x x.	x x.	x x.		x x x.	х
						X X X.	X X.	X X.	X X.	XX.	x x x.	Х



Handcrafted in Germany, certified quality



Conforms to UL-STD 1598 Certified to CSA-STD C22.2 No.250.0-08



Protective rating



Protection class III: only suitable for very low voltage supply (<50V)

Complete order number



Luminaires are suitable for mounting on ordinary flammable materials, which have an inflammation point of at least 200° C / 392° F