



CIRCOLO MINI

Housing: Aluminium profile, with L-shaped opal diffuser
 Design: SATTLER



Sizes	Size: Ø mm	Inches	LED Watt	Lumen ¹⁾	Weight ²⁾ kg/lbs	Item No.	LED	Dimming	LED	Finish	Power supply cable	Mounting version
	Ø 900 mm	35.4"	51	3.009	3.5 / 7.7	742.	x x .	x x .	x x .	x x .	x x x .	x
	Ø 1240 mm	48.8"	71	4.189	5.5 / 12.1	743.	x x .	x x .	x x .	x x .	x x x .	x
	Ø 1550 mm	61.0"	88	5.192	6.0 / 13.2	744.	x x .	x x .	x x .	x x .	x x x .	x
	Ø 1900 mm	74.8"	108	6.372	7.0 / 15.4	745.	x x .	x x .	x x .	x x .	x x x .	x


LED	Standard:	Warm-white	3000 K	x x x .	30.	x x .	x x .	x x .	x x .	x x x .	x
CRI > 90 Mac Adam 3 SELV L80 B10 100.000 h	Optional:	Neutral-white	4000 K	x x x .	40.	x x .	x x .	x x .	x x .	x x x .	x
		Extra warm-white	2700 K	x x x .	27.	x x .	x x .	x x .	x x .	x x x .	x
		Tunable white*	2700 - 6500 K	x x x .	80.	x x .	x x .	x x .	x x .	x x x .	x
		RGB colour control*		x x x .	60.	x x .	x x .	x x .	x x .	x x x .	x

*only in combination with dimming DALI, CASAMBI

Dimming	Standard:	Without Dimmer	x x x .	x x .	01.	00.	x x .	x x x .	x
	Optional:	0 - 10 V	x x x .	x x .	51.	00.	x x .	x x x .	x
		DALI	x x x .	x x .	61.	00.	x x .	x x x .	x
		CASAMBI	x x x .	x x .	81.	00.	x x .	x x x .	x



Finish	Standard:	12 white, powder coated, similar RAL 9003	Optional (Powder coated):	11 white, similar RAL 9010	10 black fine textured	30 anthracite fine textured	33 sand silver fine textured	34 bronze satined	35 gold	36 brass	37 bronze fine textured	38 copper	Optional (Premium):	22 aluminium polished	27 brush-finished aluminium	XX Custom finish	x x x .	x x .	x x .	x x .	x x x .	x
--------	-----------	---	---------------------------	----------------------------	------------------------	-----------------------------	------------------------------	-------------------	---------	----------	-------------------------	-----------	---------------------	-----------------------	-----------------------------	------------------	---------	-------	-------	-------	---------	---

Power supply cable	Standard:	000 Current-carrying F, R, T, K	Optional:	Z 70 Silver	Z 71 white	Z 72 grey	Z 73 black	Z 74 orange	Z 75 red	Z 76 green	x x x .	x x .	x x .	x x .	x x .	x
--------------------	-----------	---------------------------------	-----------	-------------	------------	-----------	------------	-------------	----------	------------	---------	-------	-------	-------	-------	---




CIRCOLO MINI

Housing: Aluminium profile, with L-shaped opal diffuser
 Design: SATTLER



Mounting version



A up to Ø 1550 mm 4-point suspension
 1900 mm 6-point suspension with external power supply unit in suspended ceiling


B up to Ø 1550 mm 4-point suspension
 1900 mm 6-point suspension with external power supply unit in separate canopy

E suspension through canopy

F Standard
 4 current-carrying steel cables. Not in combination with RGB

R Suspension with current-carrying steel cables and cavity wall box. Not in combination with RGB.

S Suspension with pendant canopy PB 375 and steel cables (a) 5000 mm / 196.8" + (b) 3000 mm / 118.1"



T Suspension with pendant canopy PB 375 and current-carrying steel cables. (a) 5000 mm / 196.8" + (b) 3000 mm / 118.1" Not in combination with RGB.

G Direct ceiling mounting 50mm / 1.9" with external power supply unit in suspended ceiling

K Suspension point as clamping unit with 4 cables and remote technical unit in suspended ceiling.

Item No.	LED	Dimming	LED	Finish	Power supply cable	Mounting version
X X X.	X X.	X X.	X X.	X X.	X X X	- .

A, B, G, R, K = Distance of external power supply unit to light fixture max. 10m / 394".
 S, T, K, E, F = Minimum suspension height half the diameter of light fixture, maximum suspension height two times diameter of light fixture

Including steel cable suspension Version F,R 3000mm/118" version S,T 5000 + 3000mm / 197"+118" and/or power supply cable 5000mm/197"

---	---	---	---	---	---	---
-----	-----	-----	-----	-----	-----	-----

Complete order number

Power supply unit:	Type / Size mm / inch L x W x H	For use with Mounting version	Protective rating
DE 1F	363 x 143 x 56 mm / 14.2 x 5.6 x 2.2"	A,G,R,K	IP 20

Input voltage for all external power supply units and canopy is 220-240 VAC 50-60 Hz

Canopy:	Type / Size mm / inch cover plate / body / H	For use with Mounting version	Protective rating
DB 230	Ø 230 / 210 / 60 mm / 9.5 / 8.3 / 2.3"	B, E, F (up to Ø 900 mm)	IP 20
DB 290	Ø 290 / 260 / 60 mm / 11.4 x 10.2 / 2.3"	B, E, F (up to Ø 1550 mm)	IP 20
DB 350	Ø 350 / 320 / 60 mm / 13.7 x 12.5 / 2.3"	B, E, F (up to Ø 1900 mm)	IP 20
PB 375	Ø 90 H 375 mm / 3.5 x 14.8"	S, T	IP 20

Colour: 12 white, similar RAL 9003, contact factory for other finishes
 USA/Canada: Canopy mounts to 4" octagonal junction box.


Optional



CASAMBI wall-switch

207. 00. 00. 00. 12. (white)
 207. 00. 00. 00. 10. (black)

Casambi wall-switch is a wireless user interface that can be configured via the Casambi app. The four target buttons can control a scene or an animation of the user's choice or simply one luminaire, one luminaire group or all lights together if so desired. Up to 4 groups may be separately programmed. It comes with a wall mounting plate. The switch may be also used on its own as it is attached to the wall plate using magnets.



Power cable cover plate for mounting version A, G

200. 00. 00. 00. 12. (white)

Consisting of a cavity ceiling box with 80mm round metal cover. Applicable to mounting version A, G.

