




## DUETTO LENS

Housing: Aluminium profile with integrated mini lens reflectors  
 Design: SATTLER



### Mounting version

Power supply units:			
Type / Size mm / inch L x W x H	For use with Mounting version	Protective rating	
DE 1F 363 x 143 x 56 mm / 14.2 x 5.6 x 2.2"	A (up to Ø 1924 mm)	IP 20	
Further sizes on request			

Canopy:			
Type/ Size mm / inch Ø cover plate / body / H	For use with Mounting version	Protective rating	
DB 230 Ø 230 / 210 / 60 mm / 9.5 / 8.3 / 2.3"	B, E (Ø 921 mm)	IP 20	
DB 290 Ø 290 / 260 / 60 mm / 11.4 x 10.2 / 2.3"	B, E (up to Ø 1924 mm)	IP 20	
PB 375 Ø 90 H 375 mm / 3.5 x 14.8"	S (up to Ø 1924 mm)	IP 20	
Colour: 12 white, similar RAL 9003, contact factory for other finishes USA/Canada: Canopy mounts to 4" octagonal junction box.			

Input voltage for all external power supply units and canopy is 100-240 VAC 50-60 Hz

A, B = Distance of external power supply unit to light fixture max. 10m / 394".

E, S = Minimum suspension height is half the diameter of light fixture, maximum suspension height two times diameter of light fixture

Including steel cable suspension 3000mm/118" and/or power supply cable 3000mm/118" version S 5000 + 3000mm / 197"+118"


### Optional



CASAMBI wall-switch

207. 00. 00. 00. 12. (white)  
 207. 00. 00. 00. 10. (black)

Casambi wall-switch is a wireless user interface that can be configured via the Casambi app. The four target buttons can control a scene or an animation of the user's choice or simply one luminaire, one luminaire group or all lights together if so desired. Up to 4 groups may be separately programmed. It comes with a wall mounting plate. The switch may be also used on its own as it is attached to the wall plate using magnets.



Power cable cover plate for mounting version A

200. 00. 00. 00. 12. (white)

Consisting of a cavity ceiling box with 80mm round metal cover. Applicable to mounting version A..

### Draft

