
LA BELLA PENDANT LAMP

Housing: Design:

Pole white. Lampshade cream white



SATTLER



	40 x 800 mm 40 x 800 mm <u>Standar</u> Optiona	13.3 /31.5" 13.3 /31.5" rd: Warm-w	4 x 10 W 8 x 10 W	LED LED	9.600 19.200	319. 319.	к х. к х.	×4. ×8.	х х. х х.	х х. х х.	х х. х х.	X X
Colour CRI >90		rd: Warm-w										^
CRI > 90	Optiona		hite	3000 K		x x x.	30.	x x.	00.	х х.	X X X.	х
Dimming		al: Extra-w Neutral-	arm-white white	2700 K 4000 K		X X X. X X X.	27. 40.	x x. x x.	00. 00.	x x. x x.	x x x. x x x.	x x
	Standar	rd: LED	Dimmable D	ALI		X X X.	х х.	бх.	X X.	x x.	х х.	Х
Finishes		12 white, simi RAL 9003	lar			X X X.	x x.	XX	х х.	12.	x x.	х
Power supply cable		Z 70 Silver				x x x.	x x.	х х.	хх.	х х.	Z70.	E
Finish clothing												
cream white						319.		1	00.	12.	Z70.	E
(Other colours are available on request)						Complete order number						

Input voltage for all external power supply units and canopy is $\ 220\text{-}240 \text{ VAC} \ 50/60 \text{ Hz}$

IP 20



LA BELLA PENDANT

22.03.21



Protection class I



Luminaires are suitable for mounting on ordinary flammable materials, which have an inflammation point of at least 200° C. / 392° F.

www.sattler-lighting.com

Technical data is subject to change. Errors and omissions excepted 1) Brutto lumen output: Losses due to diffusors and reflectors are not considered.. Lumen values refer to an ambient temperature of max. 35° Celsius / 95° Fahrenheit. 2) Weight of lights without remote technical unit or canopy.